

# Technical data sheet

External corner, for device installation trunking Rapid 45-2  
type GA-53100  
Item number: 6112423



External corner 90° aluminium for changing the direction of device installation trunking Rapid 45-2 GA...

Note:

For anodised device installation trunking and fittings made from aluminium, light colour differences caused by permitted scatter due to the material and process conditions cannot be avoided (according to DIN 17 611). The 45 mm devices can be clicked in directly. When using PC/ABS hood fittings, there may be colour differences due to the different materials.



Alu	Aluminium
EL	Anodised

## Master data


Item number	6112423
Type	GA-AS53100EL
Description 1	External corner
Description 2	Aluminium, rigid form
Manufacturer	OBO
Dimension	53x100x175
Colour	aluminium
Material	Aluminium
Surface	Anodised
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	84.1 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	11,1643 kg CO2e / 1 Piece

# Technical data sheet

External corner, for device installation trunking Rapid 45-2  
type GA-53100  
Item number: 6112423



## Dimensions



Length	175 mm
Width	100 mm
Height	53 mm

## Technical data

Number of covers	1
Version for	Base and cover
for duct width	100 mm
for trunking height	53 mm
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	no
Cover width	45 mm
Protection rating	IP40
Protective film	yes
Protection rating IK code	IK10
Symmetrical	yes
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-15 °C
Angle range, min.	90 mm